









# GIGABYTE™

## Nvidia Graphics Cards

03-Jan-19

| Model             | Memory | Photo   | Specifications   | End User |
|-------------------|--------|---|--|----------|
| GV-N710D3-2GL     | 2 GB   |    | GeForce® GT 710 GDDR3, Core Clock 954 MHz (Standard: 954 MHz), Memory Clock v2.0 1600 MHz/ v1.0 1800 MHz, Memory Bus 64 bit, Card Bus PCI-E 2.0, Digital max resolution 4096 X 2160, Multi-view 3, Card size H=21 L=144 W=68 mm, Dual-link DVI-D*1 / HDMI*1 / D-Sub*1, Recommended system power supply requirement   | \$54     |
| GV-N1030 OC GDDR5 | 2GB    |    | GeForce® GT 1030 GDDR5, Core Clock Boost: 1544 MHz/ Base: 1290 MHz in OC Mode Boost: 1518 MHz/ Base: 1265 MHz in Gaming Mode CUDA® Cores 384, Memory Clock 6008 MHz, Memory Bus 64 bit, Supports HDMI 4K @60Hz, Output DVI-D *1/ HDMI-2.0b*1 (Max Resolution: 4096x2160 @60 Hz) Smooth 4K video playback and HTML5 web browsing, Multi-view 2, Card size H=26.8 L=167.7 W=111.2 mm, PCB Form ATX, Recommended system power supply requirement 300W, One-click overclocking via AORUS Graphics Engine                         | \$97     |
| GV-1050 GDDR5     | 2GB    |    | GeForce® GTX 1050 GDDR5, Core Clock Boost: 1493 MHz/ Base: 1379 MHz in OC Mode/ Boost: 1455 MHz/ Base: 1354 MHz in Gaming Mode, CUDA® Cores 640, Memory Clock 7008 MHz, Memory Bus 128 bit, 90mm Fan Design, Card Bus PCI-E 3.0 x 16, Output Dual-link DVI-D *1/ HDMI-2.0b*1 (Max Resolution: 4096x2160 @60 Hz) Support up to 8K display (7680x4320 @60Hz), Multi-view 3, Card size H=30 L=172 W=113 mm, Recommended system power supply requirement 300W  | \$148    |
| GV-N1050 OC GDDR5 | 2GB    |    | GeForce® GTX 1050 GDDR5, Integrated with 2GB GDDR5 128bit memory, Core Clock Boost: 1518 MHz/ Base: 1404 MHz in OC Mode/ Boost: 1493 MHz/ Base: 1379 MHz in Gaming, CUDA® Cores 640, Card Bus PCI-E 3.0 x 16, Output Dual-link DVI-D *1/ HDMI-2.0b*1 (Max Resolution: 4096x2160 @60 Hz) and Support up to 8K display (7680x4320 @60 Hz), Multi-view 3, Card size H=36 L=191 W=111 mm, Recommended system power supply requirement 300W, WINDFORCE 2X with Blade Fan Design   | \$159    |
| GV-N1050 Ti WF    | 4GB    |   | GeForce® GTX 1050Ti GDDR5, Core Clock Boost: 1430MHz/ Base: 1316MHz in OC Mode/ Boost: 1392MHz/ Base: 1290MHz in Gaming Mode, CUDA® Cores 768, Memory Clock 7000 MHz, Integrated with 4GB GDDR5 128bit memory, Card Bus PCI-E 3.0 x 16, Output Dual-link DVI-D *1/ HDMI-2.0b*3 (Max Resolution: 4096x2160 @60 Hz) and Support up to 8K display (7680x4320 @60 Hz), Multi-view 4, Card size H=40 L=229 W=118 mm, Recommended system power supply requirement 300W, WINDFORCE 2X with Blade Fan Design/ Protection Back Plate  | \$217    |
| GV-N1060 OC/WF    | 3GB    |  | GeForce® GTX 1060 GDDR5, Core Clock Boost: 1797MHz/ Base: 1582MHz in OC Mode/ Boost: 1771MHz/ Base: 1556MHz in Gaming Mode, CUDA® Cores 1152, Memory Clock 8008 MHz, Integrated with 3GB GDDR5 192bit memory, Card Bus PCI-E 3.0 x 16, Dual-link DVI-D *2/ HDMI-2.0b*1 (Max Resolution: 4096x2160 @60 Hz) and Support up to Max Resolution: 7680x4320 @60 Hz, Multi-view 4, Card size H=39 L=223 W=121 mm, Recommended system power supply requirement 300W, WINDFORCE 2X with Blade Fan Design, Built with 4+1 power phases | \$270    |



