





03-Feb-19

Intel ^{9th} Gen Series LGA 1151	End User
<p>GA-Z390 AORUS MASTER Supports 9th and 8th Gen Intel® (Core™ i9/ i7/ i5/ i3/ Pentium®/ Celeron® processors for LGA1151 socket) CPU, Dual Channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory, Support for DDR4 4400(O.C.) / 4333(O.C.) / 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200(O.C.) / 3000(O.C.) / 2800(O.C.) / 2666 / 2400 / 2133 MHz, 1 x PCI x16, 1 x PCI x8, 1 x PCI x4, 3 x PCI x1, Support for NVIDIA® Quad-GPU SLI™ and 2-Way NVIDIA® SLI™, Support for AMD Quad-GPU CrossFire™ and 3-Way/2-Way AMD CrossFire™, 3 x M.2 Socket 3 connectors, 6 x SATA 6Gb/s connectors, Support for RAID 0, RAID 1, RAID 5, and RAID 10, 1 x USB Type-C™ port, with USB 3.1 Gen 2 support, 3 x USB 3.1 Gen 2 Type-A ports (red), 2 x USB 3.1 Gen 1 ports, 4 x USB 2.0/1.1 ports, 1 x HDMI port, Intel® Optane™ Memory Ready, 12 Phases IR Digital VRM Solution with PowIRstage, Advanced Thermal Design with Fins-Array Heatsink and Direct Touch Heatpipe, Onboard Intel® CNVi 802.11ac 2x2 Wave 2 Wi-Fi, 125dB SNR AMP-UP Audio with ALC1220 & High-End ESS SABRE 9118 DAC with WIMA audio capacitors, USB TurboCharger for Mobile Device Fast Charge Support, Smart Fan 5 features Multiple Temperature Sensors and Hybrid Fan Headers with FAN STOP, CEC 2019 Ready, Save Power With a Simple Click</p>	<p>\$345</p>
<p>GA-Z390 AORUS PRO WIFI Supports 9th and 8th Gen Intel® (Core™ i9/ i7/ i5/ i3/ Pentium®/ Celeron® processors for LGA1151 socket) CPU, Dual channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory, Support for DDR4 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200(O.C.) / 3000(O.C.) / 2800(O.C.) / 2666 / 2400 / 2133 MHz, 1 x PCI x16, 1 x PCI x8, 1 x PCI x4, 3 x PCI x1, Support for NVIDIA® Quad-GPU SLI™ and 2-Way NVIDIA® SLI™, Support for AMD Quad-GPU CrossFire™ and 3-Way/2-Way AMD CrossFire™, 2 x M.2 Socket 3 connectors, 6 x SATA 6Gb/s connectors, Support for RAID 0, RAID 1, RAID 5, and RAID 10, 1 x 3 x USB 3.1 Gen 1 ports, 2 x USB 3.1 Gen 2 Type-A ports (red), 1 x USB Type-C™ port, with USB 3.1 Gen 2 support, 4 x USB 2.0/1.1 ports, 1 x HDMI port, Bluetooth 5, Onboard Intel® CNVi 802.11ac 2x2 Wave 2 Wi-Fi, Smart Fan 5 features, RGB FUSION with Multi-Zone LED Light Show Design, CEC 2019 Ready, Save Power With a Simple Click</p>	<p>\$245</p>
<p>GA-Z390 GAMING SLI (rev. 1.0) Supports 9th and 8th Gen Intel® (Core™ i9/ i7/ i5/ i3/ Pentium®/ Celeron® processors for LGA1151 socket) CPU, Dual channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory, Support for DDR4 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200(O.C.) / 3000(O.C.) / 2800(O.C.) / 2666 / 2400 / 2133 MHz, Support for NVIDIA® Quad-GPU SLI™ and 2-Way NVIDIA® SLI™, Support for AMD Quad-GPU CrossFire™ and 2-Way AMD CrossFire™, 2 x M.2 Socket 3 connectors, 6 x SATA 6Gb/s connectors, Support for RAID 0, RAID 1, RAID 5, and RAID 10, 2 x USB 3.1 Gen 2 Type-A ports (red), 6 x USB 3.1 Gen 1 ports, 1 x HDMI port, New 10+2 Phases Digital PWM Design, Immersive Gaming ViBes with ALC1220-VB and High Quality Audio Capacitors, Support RGB Lighting Effect in Full Colors, Smart Fan 5 features Multiple Temperature Sensors and Hybrid Fan Headers with FAN STOP, Intel® Optane™ Memory Ready, Ultra Durable™ 25KV ESD and 15KV Surge LAN Protection, CEC 2019 Ready, Save Power With a Simple Click</p>	<p>\$205</p>
<p>GA_Z390 I AORUS PRO WIFI Supports 9th and 8th Gen Intel® (Core™ i9/ i7/ i5/ i3/ Pentium®/ Celeron® processors for LGA1151 socket) CPU, Dual Channel 2 x DDR4 DIMM sockets supporting up to 32 GB of system memory, Support for DDR4 4400(O.C.) / 4333(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200(O.C.) / 3000(O.C.) / 2800(O.C.) / 2666 / 2400 / 2133 MHz, 2 x M.2 Socket 3 connectors, 4 x SATA 6Gb/s connectors, Support for RAID 0, RAID 1, RAID 5, and RAID 10, 1 x HDMI port, 1 x USB Type-C™ port, with USB 3.1 Gen 2 support, 1 x USB Type-C™ port, with USB 3.1 Gen 2 support, 1 x USB 3.1 Gen 2 Type-A port (red), 4 x USB 3.1 Gen 1 ports, 2 x USB 2.0/1.1 ports, 1 x PCI x16, Mini-ITX Form Factor; 17.0cm x 17.0cm, BLUETOOTH 5, Onboard Intel® CNVi 802.11ac 2x2 Wave 2 Wi-Fi, RGB FUSION with Multi-Zone Addressable LED Light Show Design, Smart Fan 5 features, CEC 2019 Ready, Save Power With a Simple Click</p>	<p>\$209</p>
<p>GA-Z390 UD (rev. 1.0) Supports 9th and 8th Gen Intel® (Core™ i9/ i7/ i5/ i3/ Pentium®/ Celeron® processors for LGA1151 socket) CPU, Dual channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory, Support for DDR4 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200(O.C.) / 3000(O.C.) / 2800(O.C.) / 2666 / 2400 / 2133 MHz, 1 x PCI x16, 2 x PCI x4, 3 x PCI x1, 6 x SATA 6Gb/s connectors, Support for RAID 0, RAID 1, RAID 5, and RAID 10, 1 x HDMI port, 6 x USB 3.1 Gen 1 ports, 2 x USB 2.0/1.1 ports, ATX Form Factor; 30.5cm x 23.0cm, New 10+2 Phases Digital PWM Design, GIGABYTE Exclusive 8118 Gaming LAN with Bandwidth Management, Support RGB Light Strip in Full Colors, Smart Fan 5 features Multiple Temperature Sensors and Hybrid Fan Headers with FAN STOP, Intel® Optane™ Memory Ready, CEC 2019 Ready, Save Power With a Simple Click</p>	<p>\$165</p>

Intel 8 th Gen Series LGA 1151	End User
<p>GA-Z370 AORUS Gaming 7</p> <p>Support 8th Gen Intel® (Core™ i7 / i5 / i3 Processor for LGA 1151 socket) CPU, Dual Channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory, DDR4 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200(O.C.) / 3000(O.C.) / 2800(O.C.) / 2666 / 2133 MHz, 1PCIe x16, 1PCIe x8, 1PCIe x4, 3PCIe x1, Support 2-Way SLI, 3xM.2, 6xSATA3 6Gb/s, 2xUSB 3.1 Gen 2 with USB Type-CTM and 1 Type-A, 7xUSB 3.1, 4xUSB 2.0, Killer™ E2500 Gaming Network + Intel® Gigabyte LAN, Extreme 40 Gb/s Thunderbolt™ 3, DisplayPort HDMI (version1.4) supporting a maximum resolution of 4096x2160@30 Hz Support for up to 3 displays, USB DAC-UP 2 with Adjustable Voltage, RGB Fusion with Digital LED, Smart Headphone Amp</p>	\$295
<p>GA-Z370 HD3</p> <p>Support 8th Gen Intel® (Core™ i7 / i5 / i3 Processor for LGA 1151 socket) CPU, Dual Channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory DDR4 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200(O.C.) / 3000(O.C.) / 2800(O.C.) / 2666 / 2400 / 2133 MHz 1 PCIe x16, 2 PCIe x4, 3 PCIe x1, 1x M.2, 6 SATA3 6 Gb/s, Support for RAID 1, RAID 5 and RAID 10, 2-Way CrossFire™ Multi-Graphics, 8 x USB 3.1 Gen 1 ports, 6x USB 2.0, 1 x RGB LED strip header, 1 x serial port header, 1 x RJ-45 port, Intel® GbE Lan, HDMI (1.4 version) supporting a maximum resolution of 4096x2160@30 Hz, DVI-D, RGB Fusion LEDRGB FUSION supports RGB LED strips in 7 colors, Intel® Optane™ Memory Ready, High-End Audio Capacitors, Audio Noise Guard</p>	\$145
<p>GA-Z370M DS3H</p> <p>Supports 8th Gen Intel® (Core™ i9/ i7/ i5/ i3/ Pentium®/ Celeron® processors for LGA1151 socket) CPU, Dual channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory, Support for DDR4 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200(O.C.) / 3000(O.C.) / 2800(O.C.) / 2666 / 2400 / 2133 MHz, 1 x M.2 Socket 3 connector, 6 x SATA 6Gb/s connectors, Support for RAID 0, RAID 1, RAID 5, and RAID 10, 1 x PCI x16, 2 x PCI x1, 4 x USB 3.1 Gen 1 ports, 2 x USB 2.0/1.1 ports, 1 x PS/2 keyboard/mouse port, 1 x HDMI port, 1 x DVI-D port, Smart Fan 5, GIGABYTE UEFI DualBIOS™, Anti-Sulfur Resistors, Intel® Optane™ Memory Ready, APP Center Including Cloud Station™ Utility</p>	\$108
<p>GA-H370 AORUS GAMING 3 WIFI</p> <p>Support for 8th Generation (Intel® Core™ i7 / i5 / i3 Processor for LGA 1151 socket) CPU, Dual channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory, Support for DDR4 2666/2400/2133 MHz memory, 1 x PCI x16, 1 x PCI x4, 4 x PCI x1, 6 x SATA 6Gb/s connectors, 2 x USB Type-C™ port Support Gen1 and Gen 2, 1 x USB 3.1 Gen 2 Type-A port (red), 4 x USB 3.1 Gen 1 ports, 6 x USB 2.0/1.1 ports, 2 x M.2 Socket 3 connectors, Support for RAID 0, RAID 1, RAID 5, and RAID 10, Support for AMD Quad-GPU CrossFire™ and 2-Way AMD CrossFire™, 1 x 24-pin ATX main power connector, 1 x 8-pin ATX 12V power connector, 1 x HDMI port (supporting a maximum resolution of 4096x2160@30 Hz), 1 x DVI-D port (maximum resolution of 1920x1200@60 Hz), 8+2 Hybrid Digital PWM, Intel CNVi WIFI ready, Intel GbE LAN with cFosSpeed, RGB Fusion with Digital LEDs, Smart Fan 5, Dual Armor with Ultra Durable™, WIMA Audio Caps, CEC 2019</p>	\$155
<p>GA-H310M H</p> <p>Support for 8th Generation (Intel® Core™ i7 / i5 / i3 Processor for LGA 1151 socket) CPU, Dual Channel 2 x DDR4 DIMM sockets supporting up to 32 GB of system memory, Support DDR4 2666/2400/2133 MHz memory, 1 x PCIe x16, 2 x PCIe x1, 4 x SATA 6Gb/s connectors, 4 x USB 3.1 Gen 1 ports, 6 x USB 2.0/1.1 ports, 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz, 1 x HDMI port, supporting a maximum resolution of 4096x2160@30 Hz (1 x HDMI port, supporting a maximum resolution of 4096x2160@30 Hz), Realtek® GbE LAN chip (10/100/1000 Mbit), Smart Fan 5, Anti-Sulfur Resistor Design</p>	\$70
<p>GA-B360M AORUS GAMING 3</p> <p>Support for 8th Generation (Intel® Core™ i7 / i5 / i3 Processor for LGA 1151 socket) CPU, Dual channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory, Support for DDR4 2666/2400/2133 MHz, 1 x PCIx16, 1 x PCIx4, 1 x PCIx1, 1 x DVI-D port(supporting a maximum resolution of 1920x1200@60 Hz), 1 x HDMI port(supporting a maximum resolution of 4096x2160@30 Hz), 6 x SATA 6Gb/s connectors, 1 x USB 3.1 Gen 2 Type-A port (red) on the back panel, 5 x USB 3.1 Gen 1 ports, 6 x USB 2.0, 2 x M.2, Support for AMD Quad-GPU CrossFire™ and 2-Way AMD CrossFire™, RGB FUSION with Digital LED Light Show design, CEC 2019 Ready, Save the Power as Easy as One Click, Smart Fan 5 features Multiple Temperature Sensors and Hybrid Fan Headers with FAN STOP, DualBIOS™</p>	\$120

<p>GA-B360M GAMING HD Support for 8th Generation (Intel® Core™ i7 / i5 / i3/ Pentium® processors/ Celeron® Processor for LGA 1151 socket) CPU, Dual channel 2 x DDR4 DIMM sockets supporting up to 32 GB of system memory, Support for DDR4 2666/2400/2133 MHz, 1 x D-Sub(supporting a maximum resolution of 1920x1200@60 Hz), 1 x HDMI(supporting a maximum resolution of 4096x2160@30 Hz), 1 x M.2, 4 x SATA 6Gb/s connectors, 6 x USB 3.1 Gen 1 ports, USB 3.1 Gen2 USB Type-A, 6 x USB 2.0, New Hybrid Digital PWM Design, High Quality Audio Capacitors and Audio Noise Guard with LED Trace Path Lighting, CEC 2019 Ready, Save the Power as Easy as One Click, GIGABYTE 8118 Gaming LAN, Anti-Sulfur Resistor, Smart Fan 5, CEC 2019 ready</p>	\$87
Motherboards 2066 (7th, 6th -X/2066 Gen XTM Series) (3 Years Warranty)	End User
<p>GA-X299 AORUS Gaming 3 Support for Intel® Core™ X series processors, Quad Channal DDR4, 8DIMMs, Support for DDR4 4400(O.C.) / 4333(O.C.) / 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200(O.C.) / 3000(O.C.) / 2800(O.C.) / 2666(O.C.) / 2400 / 2133 MHz, 2 x PCIE x16, 1 x PCI x8, 2 x PCIE x4, Support for NVIDIA® Quad-GPU SLI™ and 3-Way and AMD Quad-GPU CrossFire™ and 3-Way, 10 x USB 3.1 Gen 1 ports, 4 x USB 2.0/1.1 ports, Type-A port, 2 x M.2 connectors, 8 x SATA 6Gb/s connectors, Support for RAID 0, RAID 1, RAID 5, and RAID 10, Realtek® 120dB SNR ALC1220, Intel® GbE LAN chip (10/100/1000 Mbit), Intel Gaming LAN, RGB Fusion, Digital LED strip support, Intel® Optane™ Memory Ready, VR Ready, Server-Class Digital Power Design</p>	\$310
Motherboards 1151 (7th, 6th Gen Intel® Processor) (3 Years Warranty)	End User
<p>GA-Z270X GAMING 7 Supports 7th/ 6th Generation Intel® (Core™ i7/ i5/ i3/ Pentium®/ Celeron® processors for the LGA1151 socket), Dual channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory, Support for DDR4 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200(O.C.) / 3000(O.C.) / 2800(O.C.) / 2666(O.C.) / 2400 / 2133 MHz memory, Support for NVIDIA® Quad-GPU SLI™ and 2-Way NVIDIA® SLI™, Support for AMD Quad-GPU CrossFireX™ and 3-Way/2-Way AMD CrossFire™, 1 x PCI X16, 1 x PCI X8, 1 x PCI X4, 3 x PCI x1, 2 x M.2 Socket 3 connectors, 1 x U.2 connector, 6 x SATA 6Gb/s connectors, Support for RAID 0, RAID 1, RAID 5, and RAID 10 1 x USB Type-C™, 1 x USB 3.1 Gen 2 (Type-A port (red)), 5 x USB 3.1 Gen 1, 4 x USB 2.0, 1 x DisplayPort, 1 x HDMI port, Killer™ E2500 Gaming Network + Intel® Gigabit LAN, RGB FUSION with Multi-Zone LED Light Show design, Smart Fan 5 features, GIGABYTE UEFI DualBIOS™</p>	\$278
<p>GA-H270-Gaming 3 Support 7th / 6th Gen Intel® (Core™ i7 / i5/ i3 / Pentium® / Celeron® processors for LGA 1151 socket)CPU ,Dual Channel DDR4 2400* / 2133 MHz memory, 2 PCIE x16, 2 PCIE x1 2 PCI, fast USB3.1 with Type-C & type A, Dual NVMe PCIe SSDs in RAID 0 Support, 2 M.2 with PCIe Gen3 x4, 2- Way Graphics Support with Dual Armor and Ultra Durable™ Design, Support for AMD Quad-GPU CrossFireX™ and 2-Way AMD CrossFire™ technologies, 2 SATA Express(RAID 0, RAID 1, RAID 5, and RAID 10), 6 SATA3 6Gb/s, 8 USB 3.1, 6 USB 2.0, Killer™ E2500 Gaming Network, 1 x Killer™ E2500 LAN chip (10/100/1000 Mbit), HDMI (version1.4)supporting a maximum resolution of 4096x2160@24 Hz, DVI-D ports for multiple display, 1 x serial port header, USB DAC-UP 2 with Adjustable Voltage, RGB Fusion LED, Smart Headphone Amp, Intel® Optane™ Memory Ready, VR ready</p>	\$144
<p>GA-B250M-Gaming 3 Support 7th / 6th Gen Intel® (Core™ i7 / i5/ i3 / Pentium® / Celeron® processors for LGA 1151 socket)CPU , Dual Channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory, 2- Way CrossFire™ Multi-Graphics Support, 2 PCIE x16, 2 PCIE x1, M.2 with PCIe Gen3, 6 SATA3 6Gb/s, 6 USB 3.1, 6 USB 2.0, Intel® GbE LAN, HDMI (version1.4) supporting a maximum resolution of 4096x2160@24 Hz, DVI-D, D-sub Support for up to 3 displays, 1 x serial port header, 1 x RJ-45 port, Ambient LED Light Show design, Double Locking Bracket, Intel® Optane™ Memory Ready, VR ready</p>	\$96

GA-H110M-Gaming 3 Support 7th / 6th Gen Intel® (Core™ i7 / i5/ i3/ Pentium®/ Celeron® processors for LGA 1151 socket)CPU, Dual Channel 2 x DDR4 DIMM sockets supporting up to 32 GB of system memory, 1 PCIE x16, 2 PCIE x1, 4 SATA3 6Gb/s, 4 USB 3.0, 6 USB 2.0, HDMI (version1.4)supporting a maximum resolution of 4096x2160@24 Hz, D-sub ports for multiple display, GIGABYTE Patented Double Locking Bracket, 1 x RJ-45 port, Dual Armor DIMM and PCIe Metal Shielding, Audio Noise Guard with LED Trace Path Lighting, Intel® GbE LAN	\$76
GA-H110 D3A Supports 7th / 6th Gen Intel® (Core™ i7/ i5/ i3/ Pentium®/ Celeron® processors for LGA 1151 socket) CPU, Dual channel DDR4, 2 DIMMs, sockets supporting up to 32 GB of system memory, DDR4 2400/2133 MHz, 1 x PCI Express x16 slot, 5 x PCI Express x1 slots, 1 x M.2 Socket 3 connector, 4 x SATA 6Gb/s connectors, 1 x M.2 Socket 3 connector, 1 x USB 3.1 Gen 1 header, 2 x USB 2.0/1.1 headers, 1 x serial port, 1 x D-Sub port supporting a maximum resolution of 1920x1200@60 Hz, 1 x RJ-45 port, Realtek® GbE LAN chip (10/100/1000 Mbit), Audio Noise Guard with LED Trace Path Lighting	\$100
AMD Ryzen Series Motherboard CPU Socket Type AM4	
End User	
B450 AORUS PRO WIFI (rev. 1.0) Support for AMD Ryzen™ 2nd Generation/ 1st Generation with Athlon™ (Ryzen 7/ Ryzen 5/ Ryzen 3/ Athlon), Dual channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory, Support for DDR4 3200(O.C.)/2933/2667/2400/2133 MHz, 2 x M.2 Socket 3 connectors, 6 x SATA 6Gb/s connectors, Support for RAID 0, RAID 1, and RAID 10, Support for AMD Quad-GPU CrossFire™ and 2-Way AMD CrossFire™, 4 x USB 3.1 Gen 1 ports, 1 x USB Type-C™ port, with USB 3.1 Gen 2 support, 1 x USB 3.1 Gen 2 Type-A port (red), 4 x USB 2.0/1.1 ports, 1 x PCI x16, 1 x PCI x4, 1 x PCI x1, 1 x DVI-D port, 1 x HDMI port, RGB FUSION with Multi-Zone LED Light Show Design, Supports Digital LED & RGB LED Strips, Intel® GbE LAN with cFosSpeed Internet Accelerator Software, Smart Fan 5 Features 6 Temperature Sensors and 5 Hybrid Fan Headers with FAN STOP, APP Center Including EasyTune™ and Cloud Station™ Utilities, CEC 2019 Ready, Save Power with a Simple Click	 \$165
B450M DS3H (rev. 1.0) Supports AMD Ryzen™ 2nd Generation/ 1st Generation with Athlon™ (Ryzen 7/ Ryzen 5/ Ryzen 3/ Athlon), Dual channel 4 x DDR4 DIMM sockets supporting up to 64 GB of system memory, 1 x M.2 Socket 3 connector, 4 x SATA 6Gb/s connectors, Support for RAID 0, RAID 1, and RAID 10, Support for AMD Quad-GPU CrossFire™ and 2-Way AMD CrossFire™, 4 x USB 3.1 Gen 1 ports, 4 x USB 2.0/1.1 ports, 1 x PCI x16, 1 x PCI x4, 1 x PCI x1, 1 x DVI-D port, 1 x HDMI port, High Quality Audio Capacitors and Audio Noise Guard with LED Trace Path Lighting, RGB Fusion supports RGB LED Strips in 7-Colors, Realtek® Gigabit LAN with cFosSpeed Internet Accelerator Software, Smart Fan 5 Features 5 Temperature Sensors and 2 Hybrid Fan Headers with FAN STOP, CEC 2019 Ready, Save Power with a Simple Click	 \$85
GA-A320M-S2H Supports AMD Ryzen™ & 7th Generation A-series/ Athlon™ Processors, Dual Channel, 2 x DDR4 DIMM sockets supporting up to 32 GB, DDR4 3200 (O.C.)/ 2933(O.C.)/ 2667*/ 2400/ 2133 MHz, 2 x USB 3.1 Gen 1 ports, 6 x USB 2.0/1.1 ports, 1 x M.2, 4 x SATA 6Gb/s, Support for RAID 0, RAID 1, and RAID 10, 1 x PCIE x16, 2 x PCIE x1, 1 x D-Sub port(supporting a maximum resolution of 1920x1200@60 Hz), 1 x DVI-D port(supporting a maximum resolution of 1920x1200@60 Hz), 1 x HDMI port(supporting a maximum resolution of 4096x2160@24 Hz)(1.4 version), Realtek® Gigabit LAN, Smart Fan 5 features, Simple and Easy Use	\$72

Payment Term : 14 Days Credit ဝယ်ယူသည့် Invoice ရက်စွဲမှ စတင်၍ () ပါတ်အတွင်း ငွေပေးချေပါက Cash Rebate Invoice Value ၏ (1%) ပြန်လည်ရရှိမည် ဖြစ်ပါသည်။

ဆက်သွယ်ရန် : Marketing Department ကျော်ထက်အောင် - (09-793759279, 09-693343910), E-mail-gigabytekt@sln-myanmar.com

Offer မှာယူလိုပါက Sales Department

တာဝန်ပေးခြင်း (09-777758660 , 09-428552744)

ခင်မျိုးကျော် (09-781865453), မြင်ရူမိုး (09-964818179), မင်းသစ်ကျော် (09-951107003)