






May : 2019



SHWE LAMIN NAGAR
COMPANY LIMITED.

2 Years Parts And 2 Years Service Warranty
Lamps & Lamp module 1 Year

X138WH		EndUser
Display Panel	: DLP®3D Ready	560
Resolution	: WXGA (1,280 x 800) Maximum WUXGA (1,920x1,200)	
Aspect Ratio	: 16:10 (Native), 4:3/16:9 (Supported)	
Contrast Ratio	: Dynamic Black 20,000:1	
Brightness	: 3,700 ANSI Lumens (Standard) 2,900 ANSI Lumens (Eco)	
Lamp Life	: 4,000 Hours (Standard), 6,000 Hours (ECO) 10,000 Hours (ExtremeEco)	
Keystone Correction	: +/- 40 Degree (Vertical ,Manual)	
Throw Ratio	: 1.54~1.72 (60" @2m)	
Input	: Analog RGB/Component Video (D-Sub), HDMI, PC Audio	 
Output	: DC Out (5V/2A), USB Type A)	COLOUR : Black
X1226H		EndUser
Display Panel	: DLP®3D Ready	515
Resolution	: XGA (1,024 x 768) Maximum WUXGA (1,920x1,200)	
Aspect Ratio	: 4:3 (Native), 16:9 (Supported)	
Contrast Ratio	: Dynamic Black 20,000:1	
Brightness	: 4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco) (Compliant with ISO 21118 Standard)	
Lamp Life	: 4,500 Hours (Standard), 10,000 Hours (ECO) 15,000 Hours (ExtremeEco)	
Keystone Correction	: +/- 40 Degree (Vertical ,Manual & Auto)	
Throw Ratio	: 1.94~2.16 (51" @2m)	
Input	: Analog RGB/Component Video (D-Sub), RCA, S-Video, HDMI, PC Audio	 
Output	: RGB, DC Out, PC Audio	COLOUR : Black
X1126H		EndUser
Display Panel	: DLP®3D Ready	459
Resolution	: SVGA (800 x 600) Maximum WUXGA (1,920x1,200)	
Aspect Ratio	: 4:3 (Native), 16:9 (Supported)	455
Contrast Ratio	: Dynamic Black 20,000:1	
Brightness	: 4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco) (Compliant with ISO 21118 Standard)	
Lamp Life	: 4,500 Hours (Standard), 10,000 Hours (ECO) 15,000 Hours (ExtremeEco)	
Keystone Correction	: +/- 40 Degree (Vertical ,Manual & Auto)	
Throw Ratio	: 1.94~2.16 (51" @2m)	
Input	: Analog RGB/Component Video (D-Sub), RCA, S-Video, HDMI, PC Audio	 
Output	: RGB, DC Out, PC Audio	COLOUR : Black
X128H		EndUser
Display Panel	: 0.55" DarkChip TM 3 MD	435
Resolution	: XGA (1.024x768); Maximum: WUXGA (1,920x1,200)	
Aspect Ratio	: 4:3 (Native) , 16:9 (Supported)	419
Contrast Ratio	: 20,000:1	
Brightness	: 3,600 ANSI Lumens(Standard), 2,800 ANSL Lumens (ECO)	
Lamp Life	: 4,000 Hours (Standard); 6,000 Hours (Eco), 10,000 Hours (ExtremeEco)	
Throw Ratio	: 1.94 ~ 2.16 (51" @2m)	
Noise Level	30 dBA (Standard), 24 dBA (ECO)	
Keystone Correction	: +/-40 Degrees (Vertical, Manual)	
Input Interface	: Analog RGB/Component Video (D-sub) : Composite Video, HDMI, PC Audio	 
Output	: DC Out (5V/2A, USB Type A) x1	COLOUR : Black



May : 2019

Two Years Warranty (Parts and Service)

X1123H

Display Panel : DLP @3D Ready
 Resolution : SVGA (800 x 600), Maximum WUXGA (1,920 x 1,200)
 Aspect Ratio : 4:3 (Native) , 16:9 (Supported)
 Contrast Ratio : Dynamic Black 20,000.1
 Brightness : 3,600 ANSI Lumens(Standard), 2,880 ANSL Lumens (ECO)
 (Compliant with ISO 21118 standard)
 Lamp Life : 5,000 Hours (Standard); 10,000 Hours (Eco),
 15,000 Hours (ExtremeEco)
 Throw Ratio : 1.96 ~ 2.15 (50"@2m)
 Noise Level : 30 dBA (Standard), 26 dBA (ECO)
 Keystone Correction : +/-40 Degrees (Vertical, Manual)
 Input Interface : Analog RGB/Component Video (D-sub)
 : Composite Video, HDMI, PC Audio
 Output : Analog RGB (D-sub) , PC Audio (Stereo mini jack)

EndUser

390



COLOUR : Black



X118H

Display Panel : DLP @3D Ready
 Resolution : SVGA (800 x 600), Maximum WUXGA (1,920 x 1,200)
 Contrast Ratio : Dynamic Black 20,000.1
 Brightness : 3,600 ANSI Lumens(Standard), 2,800 ANSL Lumens (ECO)
 Lamp Life : 4,000 Hours (Standard); 6,000 Hours (Eco),
 10,000 Hours (ExtremeEco)
 Throw Ratio : 1.94 ~ 2.16 (51"@2m)
 Noise Level : 30 dBA (Standard), 24 dBA (ECO)
 Keystone Correction : +/-40 Degrees (Vertical, Manual)
 Input Interface : Analog RGB/Component Video (D-sub)
 : Composite Video, HDMI, PC Audio
 Output : DC Out (5V/2A, USB Type A) x1

EndUser

~~385~~

380



COLOUR : Black



P1150

Display Panel : DLP™
 Resolution : SVGA (800 x 600) Maximum WUXGA (1,920 x 1,200)
 Aspect Ratio : 4:3 (Native), 16:9 (Supported)
 Contrast Ratio : Dynamic Black 20,000:1
 Brightness : 3,600 ANSI Lumens (Standard), 2,880ANSI Lumens (ECO)
 (Compliant with ISO 21118 Standard)
 Lamp Life : 5,000 Hours (Standard), 10,000 Hours (ECO)
 15,000 Hours (ExtremeEco)
 Noise Level : 30 dBA (Standard), 26 dBA (ECO)
 Keystone Correction : +/- 40 Degree (Vertical ,Manual & Auto)
 Throw Ratio : 1.96 ~ 2.15 (50" @ 2m)
 Input : Analog RGB/Component Video (D-sub) x 2
 Composite Video,HDMI (Video, Audio, HDCP)
 HDMI/MHL,PC Audio
 Output : Analog RGB (D-sub), PC Audio, DC Out

EndUser

~~400~~

389



COLOUR : White



"Acer Projection Screen 70

Cleanable surface
 Easy for installation on wall or ceiling with
 attached mounting brackets
 Cleanable surface
 Surface : Matt White
 Gain : 1.0
 Size : 70" x70"

EndUser

55

