



X138WH		EndUser
Display Panel	: DLP@3D Ready	560 499
Resolution	: WXGA (1,280 x 800) Maximum WUXGA (1,920x1,200)	
Aspect Ratio	: 16:10 (Native), 4:3/16:9 (Supported)	
Contrast Ratio	: Dynamic Black 20,000:1	
Brightness	: 3,700 ANSI Lumens (Standard) 2,900 ANSI Lumens (Eco)	
Lamp Life	: 4,000 Hours (Standard), 6,000 Hours (ECO) 10,000 Hours (ExtremeEco)	
Keystone Correction	: +/- 40 Degree (Vertical ,Manual)	
Throw Ratio	: 1.54~1.72 (60"@2m)	
Input	: Analog RGB/Component Video (D-Sub), HDMI, PC Audio	 
Output	: DC Out (5V/2A), USB Type A)	COLOUR: Black
X1226H		EndUser
Display Panel	: DLP@3D Ready	515
Resolution	: XGA (1,024 x 768) Maximum WUXGA (1,920x1,200)	
Aspect Ratio	: 4:3 (Native), 16:9 (Supported)	
Contrast Ratio	: Dynamic Black 20,000:1	
Brightness	: 4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco) (Compliant with ISO 21118 Standard)	
Lamp Life	: 4,500 Hours (Standard), 10,000 Hours (ECO) 15,000 Hours (ExtremeEco)	
Keystone Correction	: +/- 40 Degree (Vertical ,Manual & Auto)	
Throw Ratio	: 1.94~2.16 (51"@2m)	
Input	: Analog RGB/Component Video (D-Sub), RCA, S-Video, HDMI, PC Audio	 
Output	: RGB, DC Out, PC Audio	COLOUR: Black
X1126H		EndUser
Display Panel	: DLP@3D Ready	455
Resolution	: SVGA (800 x 600) Maximum WUXGA (1,920x1,200)	
Aspect Ratio	: 4:3 (Native), 16:9 (Supported)	
Contrast Ratio	: Dynamic Black 20,000:1	
Brightness	: 4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco) (Compliant with ISO 21118 Standard)	
Lamp Life	: 4,500 Hours (Standard), 10,000 Hours (ECO) 15,000 Hours (ExtremeEco)	
Keystone Correction	: +/- 40 Degree (Vertical ,Manual & Auto)	
Throw Ratio	: 1.94~2.16 (51"@2m)	
Input	: Analog RGB/Component Video (D-Sub), RCA, S-Video, HDMI, PC Audio	 
Output	: RGB, DC Out, PC Audio	COLOUR: Black
X128H		EndUser
Display Panel	: 0.55" DarkChip TM 3 MD	419
Resolution	: XGA (1,024x768); Maximum: WUXGA (1,920x1,200)	
Aspect Ratio	: 4:3 (Native) , 16:9 (Supported)	
Contrast Ratio	: 20,000:1	
Brightness	: 3,600 ANSI Lumens(Standard), 2,800 ANSL Lumens (ECO)	
Lamp Life	: 4,000 Hours (Standard); 6,000 Hours (Eco), 10,000 Hours (ExtremeEco)	
Throw Ratio	: 1.94 ~ 2.16 (51"@2m)	
Noise Level	30 dBA (Standard), 24 dBA (ECO)	
Keystone Correction	: +/-40 Degrees (Vertical, Manual)	
Input Interface	: Analog RGB/Component Video (D-sub) : Composite Video, HDMI, PC Audio	 
Output	: DC Out (5V/2A, USB Type A) x1	COLOUR: Black



June : 2019

Two Years Warranty (Parts and Service)

X1123H		EndUser
Display Panel	: DLP @3D Ready	390
Resolution	: SVGA (800 x 600), Maximum WUXGA (1,920 x 1,200)	
Aspect Ratio	: 4:3 (Native) , 16:9 (Supported)	
Contrast Ratio	: Dynamic Black 20,000:1	
Brightness	: 3,600 ANSI Lumens(Standard), 2,880 ANSL Lumens (ECO) (Compliant with ISO 21118 standard)	
Lamp Life	: 5,000 Hours (Standard); 10,000 Hours (Eco), 15,000 Hours (ExtremeEco)	
Throw Ratio	: 1.96 ~ 2.15 (50"@2m)	
Noise Level	: 30 dBA (Standard), 26 dBA (ECO)	COLOUR: Black
Keystone Correction	: +/-40 Degrees (Vertical, Manual)	
Input Interface	: Analog RGB/Component Video (D-sub) : Composite Video, HDMI, PC Audio	
Output	: Analog RGB (D-sub) , PC Audio (Stereo mini jack)	
X118H		EndUser
Display Panel	: DLP @3D Ready	380 339
Resolution	: SVGA (800 x 600), Maximum WUXGA (1,920 x 1,200)	
Contrast Ratio	: Dynamic Black 20,000:1	
Brightness	: 3,600 ANSI Lumens(Standard), 2,800 ANSL Lumens (ECO)	
Lamp Life	: 4,000 Hours (Standard); 6,000 Hours (Eco), 10,000 Hours (ExtremeEco)	
Throw Ratio	: 1.94 ~ 2.16 (51"@2m)	
Noise Level	: 30 dBA (Standard), 24 dBA (ECO)	COLOUR: Black
Keystone Correction	: +/-40 Degrees (Vertical, Manual)	
Input Interface	: Analog RGB/Component Video (D-sub) : Composite Video, HDMI, PC Audio	
Output	: DC Out (5V/2A, USB Type A) x1	
P1150		EndUser
Display Panel	: DLP™	389
Resolution	: SVGA (800 x 600) Maximum WUXGA (1,920 x 1,200)	
Aspect Ratio	: 4:3 (Native), 16:9 (Supported)	
Contrast Ratio	: Dynamic Black 20,000:1	
Brightness	: 3,600 ANSI Lumens (Standard), 2,880ANSI Lumens (ECO) (Compliant with ISO 21118 Standard)	
Lamp Life	: 5,000 Hours (Standard), 10,000 Hours (ECO) 15,000 Hours (ExtremeEco)	
Noise Level	: 30 dBA (Standard), 26 dBA (ECO)	
Keystone Correction	: +/- 40 Degree (Vertical ,Manual & Auto)	
Throw Ratio	: 1.96 ~ 2.15 (50" @ 2m)	
Input	: Analog RGB/Component Video (D-sub) x 2 : Composite Video,HDMI (Video, Audio, HDCP) : HDMI/MHL,PC Audio	COLOUR: White
Output	: Analog RGB (D-sub), PC Audio, DC Out	
"Acer Projection Screen 70		EndUser
Cleanable surface		55
Easy for installation on wall or ceiling with attached mounting brackets		
Cleanable surface		
Surface	: Matt White	
Gain	: 1.0	
Size	: 70" x70"	

Price may be changed with or without prior notice.Thank you !