



**2 Years Parts And 2 Years Service Warranty
Lamps & Lamp module 1 Year**

X138WH

Display Panel : DLP@3D Ready
 Resolution : WXGA (1,280 x 800) Maximum WUXGA (1,920x1,200)
 Aspect Ratio : 16:10 (Native), 4:3/16:9 (Supported)
 Contrast Ratio : Dynamic Black 20,000:1
 Brightness : 3,700 ANSI Lumens (Standard) 2,900 ANSI Lumens (Eco)
 Lamp Life : 4,000 Hours (Standard),6,000 Hours (ECO)
 10,000 Hours (ExtremeEco)
 Keystone Correction : +/- 40 Degree (Vertical ,Manual)
 Throw Ratio : 1.54~1.72 (60"@2m)
 Input : Analog RGB/Component Video (D-Sub),
 HDMI, PC Audio
 Output : DC Out (5V/2A), USB Type A)

EndUser
499



COLOUR: Black

X1226H

Display Panel : DLP@3D Ready
 Resolution : XGA (1,024 x 768) Maximum WUXGA (1,920x1,200)
 Aspect Ratio : 4:3 (Native), 16:9 (Supported)
 Contrast Ratio : Dynamic Black 20,000:1
 Brightness : 4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco)
 (Compliant with ISO 21118 Standard)
 Lamp Life : 4,500 Hours (Standard),10,000 Hours (ECO)
 15,000 Hours (ExtremeEco)
 Keystone Correction : +/- 40 Degree (Vertical ,Manual & Auto)
 Throw Ratio : 1.94~2.16 (51"@2m)
 Input : Analog RGB/Component Video (D-Sub),
 RCA, S-Video, HDMI, PC Audio
 Output : RGB, DC Out, PC Audio

EndUser
515



COLOUR: Black

X1126H

Display Panel : DLP@3D Ready
 Resolution : SVGA (800 x 600) Maximum WUXGA (1,920x1,200)
 Aspect Ratio : 4:3 (Native), 16:9 (Supported)
 Contrast Ratio : Dynamic Black 20,000:1
 Brightness : 4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco)
 (Compliant with ISO 21118 Standard)
 Lamp Life : 4,500 Hours (Standard),10,000 Hours (ECO)
 15,000 Hours (ExtremeEco)
 Keystone Correction : +/- 40 Degree (Vertical ,Manual & Auto)
 Throw Ratio : 1.94~2.16 (51"@2m)
 Input : Analog RGB/Component Video (D-Sub),
 RCA, S-Video, HDMI, PC Audio
 Output : RGB, DC Out, PC Audio

EndUser
455



COLOUR: Black

X128H

Display Panel : 0.55" DarkChip TM 3 MD
 Resolution : XGA (1,024x768); Maximum: WUXGA (1,920x1,200)
 Aspect Ratio : 4:3 (Native) , 16:9 (Supported)
 Contrast Ratio : 20,000:1
 Brightness : 3,600 ANSI Lumens(Standard), 2,800 ANSL Lumens (ECO)
 Lamp Life : 4,000 Hours (Standard); 6,000 Hours (Eco),
 10,000 Hours (ExtremeEco)
 Throw Ratio : 1.94 ~ 2.16 (51"@2m)
 Noise Level : 30 dBA (Standard), 24 dBA (ECO)
 Keystone Correction : +/-40 Degrees (Vertical, Manual)
 Input Interface : Analog RGB/Component Video (D-sub)
 : Composite Video, HDMI, PC Audio
 Output : DC Out (5V/2A, USB Type A) x1

EndUser
419



COLOUR: Black



July : 2019

Two Years Warranty (Parts and Service)

X1123H

Display Panel : DLP @3D Ready
 Resolution : SVGA (800 x 600), Maximum WUXGA (1,920 x 1,200)
 Aspect Ratio : 4:3 (Native) , 16:9 (Supported)
 Contrast Ratio : Dynamic Black 20,000:1
 Brightness : 3,600 ANSI Lumens(Standard), 2,880 ANSL Lumens (ECO)
 (Compliant with ISO 21118 standard)
 Lamp Life : 5,000 Hours (Standard); 10,000 Hours (Eco),
 15,000 Hours (ExtremeEco)
 Throw Ratio : 1.96 ~ 2.15 (50"@2m)
 Noise Level : 30 dBA (Standard), 26 dBA (ECO)
 Keystone Correction : +/-40 Degrees (Vertical, Manual)
 Input Interface : Analog RGB/Component Video (D-sub)
 : Composite Video, HDMI, PC Audio
 Output : Analog RGB (D-sub) , PC Audio (Stereo mini jack)



COLOUR: Black



EndUser

390

X118H

Display Panel : DLP @3D Ready
 Resolution : SVGA (800 x 600), Maximum WUXGA (1,920 x 1,200)
 Contrast Ratio : Dynamic Black 20,000:1
 Brightness : 3,600 ANSI Lumens(Standard), 2,800 ANSL Lumens (ECO)
 Lamp Life : 4,000 Hours (Standard); 6,000 Hours (Eco),
 10,000 Hours (ExtremeEco)
 Throw Ratio : 1.94 ~ 2.16 (51"@2m)
 Noise Level : 30 dBA (Standard), 24 dBA (ECO)
 Keystone Correction : +/-40 Degrees (Vertical, Manual)
 Input Interface : Analog RGB/Component Video (D-sub)
 : Composite Video, HDMI, PC Audio
 Output : DC Out (5V/2A, USB Type A) x1



COLOUR: Black



EndUser

339

P1150

Display Panel : DLP™
 Resolution : SVGA (800 x 600) Maximum WUXGA (1,920 x 1,200)
 Aspect Ratio : 4:3 (Native), 16:9 (Supported)
 Contrast Ratio : Dynamic Black 20,000:1
 Brightness : 3,600 ANSI Lumens (Standard), 2,880ANSI Lumens (ECO)
 (Compliant with ISO 21118 Standard)
 Lamp Life : 5,000 Hours (Standard), 10,000 Hours (ECO)
 15,000 Hours (ExtremeEco)
 Noise Level : 30 dBA (Standard), 26 dBA (ECO)
 Keystone Correction : +/- 40 Degree (Vertical ,Manual & Auto)
 Throw Ratio : 1.96 ~ 2.15 (50" @ 2m)
 Input : Analog RGB/Component Video (D-sub) x 2
 Composite Video,HDMI (Video, Audio, HDCP)
 HDMI/MHL,PC Audio
 Output : Analog RGB (D-sub), PC Audio, DC Out



COLOUR: White



EndUser

389

"Acer Projection Screen 70

Cleanable surface
 Easy for installation on wall or ceiling with
 attached mounting brackets
 Cleanable surface
 Surface : Matt White
 Gain : 1.0
 Size : 70" x70"



EndUser

55

Price may be changed with or without prior notice.Thank you !