









# SHWE LAMIN NAGAR COMPANY LIMITED.



No. 200/208, Ground Floor (Room No.002), 35<sup>th</sup> St. (Upper), Kyauktada Tsp., Yangon.  
 Head Office +951-255655, +951-255714, +959-252229400, +959-252229500  
 E-mail : shwelaminagar@sln-myanmar.com | Website : www.sln-myanmar.com | Facebook : SLN Myanmar

March : 2020

**2 Years Parts And 2 Years Service Warranty  
 Lamps & Lamp module 1 Year**

<b>X1226H</b>	Display Panel : DLP®3D Ready Resolution : XGA (1,024 x 768) Maximum WUXGA (1,920x1,200) Aspect Ratio : 4:3 (Native), 16:9 (Supported) Contrast Ratio : Dynamic Black 20,000:1 Brightness : 4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco) (Compliant with ISO 21118 Standard) Lamp Life : 4,500 Hours (Standard),10,000 Hours (ECO) 15,000 Hours (ExtremeEco) Keystone Correction : +/- 40 Degree ( Vertical ,Manual & Auto) Throw Ratio : 1.94~2.16 (51" @2m) Input : Analog RGB/Component Video (D-Sub), RCA, S-Video, HDMI, PC Audio Output : RGB, DC Out, PC Audio	 <b>COLOUR: Black</b>	 <b>EndUser</b> <b>469</b>
<b>X138WH</b>	Display Panel : DLP®3D Ready Resolution : WXGA (1,280 x 800) Maximum WUXGA (1,920x1,200) Aspect Ratio : 16:10 (Native), 4:3/16:9 (Supported) Contrast Ratio : Dynamic Black 20,000:1 Brightness : 3,700 ANSI Lumens (Standard) 2,900 ANSI Lumens (Eco) Lamp Life : 4,000 Hours (Standard),6,000 Hours (ECO) 10,000 Hours (ExtremeEco) Keystone Correction : +/- 40 Degree ( Vertical ,Manual ) Throw Ratio : 1.54~1.72 (60" @2m) Input : Analog RGB/Component Video (D-Sub), HDMI, PC Audio Output : DC Out (5V/2A), USB Type A)	 <b>COLOUR: Black</b>	 <b>EndUser</b> <b>449</b>
<b>X1126H</b>	Display Panel : DLP®3D Ready Resolution : SVGA (800 x 600) Maximum WUXGA (1,920x1,200) Aspect Ratio : 4:3 (Native), 16:9 (Supported) Contrast Ratio : Dynamic Black 20,000:1 Brightness : 4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco) (Compliant with ISO 21118 Standard) Lamp Life : 4,500 Hours (Standard),10,000 Hours (ECO) 15,000 Hours (ExtremeEco) Keystone Correction : +/- 40 Degree ( Vertical ,Manual & Auto) Throw Ratio : 1.94~2.16 (51" @2m) Input : Analog RGB/Component Video (D-Sub), RCA, S-Video, HDMI, PC Audio Output : RGB, DC Out, PC Audio	 <b>COLOUR: Black</b>	<b>EndUser</b> <del>409</del> <b>319</b>
<b>X128H</b>	Display Panel : 0.55" DarkChip TM 3 MD Resolution : XGA (1.024x768); Maximum: WUXGA (1,920x1,200) Aspect Ratio : 4:3 (Native) , 16:9 (Supported) Contrast Ratio : 20,000:1 Brightness : 3,600 ANSI Lumens(Standard), 2,800 ANSL Lumens (ECO) Lamp Life : 4,000 Hours (Standard); 6,000 Hours (Eco), 10,000 Hours (ExtremeEco) Throw Ratio : 1.94 ~ 2.16 (51" @2m) Noise Level : 30 dBA (Standard), 24 dBA (ECO) Keystone Correction : +/-40 Degrees (Vertical, Manual) Input Interface : Analog RGB/Component Video (D-sub) : Composite Video, HDMI, PC Audio Output : DC Out (5V/2A, USB Type A) x1	 <b>COLOUR: Black</b>	<b>EndUser</b> <b>360</b>

**March : 2020**

**X1123H**

Display Panel : DLP ®3D Ready  
 Resolution : SVGA (800 x 600), Maximum WUXGA (1,920 x 1,200)  
 Aspect Ratio : 4:3 (Native) , 16:9 (Supported)  
 Contrast Ratio : Dynamic Black 20,000:1  
 Brightness : 3,600 ANSI Lumens(Standard), 2,880 ANSL Lumens (ECO)  
 (Compliant with ISO 21118 standard)  
 Lamp Life : 5,000 Hours (Standard); 10,000 Hours (Eco),  
 15,000 Hours (ExtremeEco)  
 Throw Ratio : 1.96 ~ 2.15 (50"@2m)  
 Noise Level : 30 dBA (Standard), 26 dBA (ECO)  
 Keystone Correction : +/-40 Degrees (Vertical, Manual)  
 Input Interface : Analog RGB/Component Video (D-sub)  
 : Composite Video, HDMI, PC Audio  
 Output : Analog RGB (D-sub) , PC Audio (Stereo mini jack)

**EndUser**

**309**



**COLOUR : Black**



**P1150**

Display Panel : DLP™  
 Resolution : SVGA (800 x 600) Maximum WUXGA (1,920 x 1,200)  
 Aspect Ratio : 4:3 (Native), 16:9 (Supported)  
 Contrast Ratio : Dynamic Black 20,000:1  
 Brightness : 3,600 ANSI Lumens (Standard), 2,880ANSI Lumens (ECO)  
 (Compliant with ISO 21118 Standard)  
 Lamp Life : 5,000 Hours (Standard), 10,000 Hours (ECO)  
 15,000 Hours (ExtremeEco)  
 Noise Level : 30 dBA (Standard), 26 dBA (ECO)  
 Keystone Correction : +/- 40 Degree ( Vertical ,Manual & Auto)  
 Throw Ratio : 1.96 ~ 2.15 (50" @ 2m)  
 Input : Analog RGB/Component Video (D-sub) x 2  
 Composite Video,HDMI (Video, Audio, HDCP)  
 HDMI/MHL,PC Audio  
 Output : Analog RGB (D-sub), PC Audio, DC Out

**EndUser**

**355**



**COLOUR : White**



**"Acer Projection Screen 70**

Cleanable surface  
 Easy for installation on wall or ceiling with  
 attached mounting brackets  
 Cleanable surface  
 Surface : Matt White  
 Gain : 1.0  
 Size : 70" x70"



**EndUser**

**55**

*Price may be changed with or without prior notice.Thank you !*