



SHWE LAMIN NAGAR COMPANY LIMITED.



No. 200/208, Ground Floor (Room No.002), 35th St. (Upper), Kyauktada Tsp., Yangon.



Head Office +951-2556655, +951-255714, +959-252229400, +959-252229500

E-mail : shwelaminagar@sln-myanmar.com | Website : www.sln-myanmar.com | Facebook : SLN Myanmar

Two Years Parts and Services Warranty (Lamps & Lamps mouldle One Year)

October : 2020

DEALER END USER

<p>X1226H</p> 	<p>Display Panel : DLP®3D Ready Resolution : XGA (1,024 x 768) Maximum WUXGA (1,920x1,200) Aspect Ratio : 4:3 (Native), 16:9 (Supported) Contrast Ratio : Dynamic Black 20,000:1 Brightness : 4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco) (Compliant with ISO 21118 Standard) Lamp Life : 4,500 Hours (Standard),10,000 Hours (ECO) 15,000 Hours (ExtremeEco) Keystone Correction : +/- 40 Degree (Vertical ,Manual & Auto) Throw Ratio : 1.94~2.16 (51"@2m) Input : Analog RGB/Component Video (D-Sub), RCA, S-Video, HDMI, PC Audio Output : RGB, DC Out, PC Audio</p> <p style="text-align: right;"> Colour : Black</p>	399	419
<p>X1126H</p> 	<p>Display Panel : DLP®3D Ready Resolution : SVGA (800 x 600) Maximum WUXGA (1,920x1,200) Aspect Ratio : 4:3 (Native), 16:9 (Supported) Contrast Ratio : Dynamic Black 20,000:1 Brightness : 4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco) (Compliant with ISO 21118 Standard) Lamp Life : 4,500 Hours (Standard),10,000 Hours (ECO) 15,000 Hours (ExtremeEco) Keystone Correction : +/- 40 Degree (Vertical ,Manual & Auto) Throw Ratio : 1.94~2.16 (51"@2m) Input : Analog RGB/Component Video (D-Sub), RCA, S-Video, HDMI, PC Audio Output : RGB, DC Out, PC Audio</p> <p style="text-align: right;"> Colour : Black</p>	299	319
<p>P5330W</p> 	<p>Display Panel : DLP® Resolution : WXGA (1,280 x 800) Maximum WUXGA (1,920x1,200) Aspect Ratio : 16:10 (Native), 4:3/16:9 (Supported) Contrast Ratio : 20,000:1 Brightness : 4,500 ANSI Lumens (Standard), 3,600 ANSI Lumens (Eco) Lamp Life : 4,000 Hours (Standard), 10,000 Hours (ECO) 15,000 Hours (ExtremeEco) Keystone Correction : +/- 20 Degree (Vertical ,Manual & Auto), +/- 20 Degree (Horizontal ,Manual), 4-Corner adjustment Throw Ratio : 1.19~1.54 (78"@2m) Input : Analog RGB/Component Video (D-Sub)x2, Composite Video (RCA)x1, HDMI, HDMI/HML, PC Audio Output : DC Out (5V/2A, USB Type A)x1, PC Audio, Analog RGB (D-sub)</p> <p style="text-align: right;"> Colour : White</p>	650	670

* Price may be changed with or without prior notice !

!***!