



# SHWE LAMIN NAGAR COMPANY LIMITED.



No. 200/208, Ground Floor (Room No.002), 35<sup>th</sup> St. (Upper), Kyauktada Tsp., Yangon.  
Head Office +951-255655, +951-255714, +959-252229400, +959-252229500  
E-mail : shwelaminnagar@sln-myanmar.com | Website : www.sln-myanmar.com | Facebook : SLN Myanmar

*Two Years Part & ServiceWarranty  
( Lamps & Lamps module are One Year )*

July : 2021

End User

 <p><b><u>X1126AH</u></b></p>	<p>Display Panel : DLP®3D Ready  Resolution : SVGA (800 x 600) Maximum WUXGA (1,920x1,200)  Aspect Ratio : 4:3 (Native), 16:9 (Supported)  Contrast Ratio : Dynamic Black 20,000:1  Brightness : 4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco)  (Compliant with ISO 21118 Standard)  Lamp Life : 4,500 Hours (Standard),10,000 Hours (ECO)  15,000 Hours (ExtremeEco)  Keystone Correction : +/- 40 Degree ( Vertical ,Manual &amp; Auto)  Throw Ratio : 1.94~2.16 (51" @2m)  Input : Analog RGB/Component Video (D-Sub),  RCA, S-Video, HDMI, PC Audio  Output : RGB, DC Out, PC Audio  Colour : Black</p> 	<p>319</p>
 <p><b><u>X1226AH</u></b></p>	<p>Display Panel : DLP®3D Ready  Resolution : XGA (1,024 x 768) Maximum WUXGA (1,920x1,200)  Aspect Ratio : 4:3 (Native), 16:9 (Supported)  Contrast Ratio : <b>Dynamic Black 20,000:1</b>  Brightness : <b>4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco)</b>  <b>(Compliant with ISO 21118 Standard)</b>  Lamp Life : 4,500 Hours (Standard),10,000 Hours (ECO)  15,000 Hours (ExtremeEco)  Keystone Correction : +/- 40 Degree ( Vertical ,Manual &amp; Auto)  Throw Ratio : 1.94~2.16 (51" @2m)  Input : Analog RGB/Component Video (D-Sub),  RCA, S-Video, HDMI, PC Audio  Output : RGB, DC Out, PC Audio  Colour : Black</p> 	<p>419</p>
 <p><b><u>X1326AWH</u></b></p>	<p>Display Panel : DLP®3D Ready  Resolution : WXGA (1,280 x 800) Maximum WUXGA (1,920x1,200)  Aspect Ratio : 16:10 (Native), 4:3/16:9 (Supported)  Contrast Ratio : 20,000:1  Brightness : 4,000 ANSI Lumens (Standard), 3,200 ANSI Lumens (Eco)  Lamp Life : 6,000 Hours (Standard),7,000 Hours (ECO)  10,000 Hours (ExtremeEco)  Keystone Correction : +/- 40 Degree ( Vertical ,Manual )  Throw Ratio : 1.54~1.72 (60" @2m)  Input : Analog RGB/Component Video (D-Sub),  Composite Video, HDMI, PC Audio  Output : DC Out (5V/1A), PC Audio, Analog RGB ( D-sub )  Colour : Black</p>	<p>509</p>
 <p><b><u>P5330W</u></b></p>	<p>Display Panel : DLP®  Resolution : WXGA (1,280 x 800) Maximum WUXGA (1,920x1,200)  Aspect Ratio : 16:10 (Native), 4:3/16:9 (Supported)  Contrast Ratio : 20,000:1  Brightness : 4,500 ANSI Lumens (Standard), 3,600 ANSI Lumens (Eco)  Lamp Life : 4,000 Hours (Standard), 10,000 Hours (ECO)  15,000 Hours (ExtremeEco)  Keystone Correction : +/- 20 Degree ( Vertical ,Manual &amp; Auto ),  +/- 20 Degree ( Horizontal ,Manual ), 4-Corner adjustment  Throw Ratio : 1.19~1.54 (78" @2m)  Input : Analog RGB/Component Video (D-Sub)x2,  Composite Video ( RCA )x1, HDMI, HDMI/HML, PC Audio  Output : DC Out (5V/2A, USB Type A)x1, PC Audio, Analog RGB ( D-sub )  Colour : White</p>	<p>670</p>

**\* Price may be changed with or without prior notice !**