SHWE LAMIN NAGAR COMPANY LIMITED.

No. 200/208, Ground Floor (Room No.002), 35th St. (Upper), Kyauktada Tsp., Yangon.
Head Office +951-255655, +951-255714, +959-252229400, +959-252229500
E-mail : shwelaminnagar@sln-myanmar.com | Website : www.sln-myanmar.com | Facebook : SLN Myanmar

Two Years Part & ServiceWarranty
(Lamps & Lamps module are One Year)

June : 2022

		End User
P5330W 	Display Panel : DLP® Resolution : WXGA (1,280 x 800) Maximum WUXGA (1,920x1,200) Aspect Ratio : 16:10 (Native), 4:3/16:9 (Supported) Contrast Ratio : 20,000:1 Brightness : 4,500 ANSI Lumens (Standard), 3,600 ANSI Lumens (Eco) Lamp Life : 4,000 Hours (Standard), 10,000 Hours (ECO) 15,000 Hours (ExtremeEco) Keystone Correction : +/- 20 Degree (Vertical ,Manual & Auto), +/- 20 Degree (Horizontal ,Manual), 4-Corner adjustment Throw Ratio : 1.19~1.54 (78"@2m) Input : Analog RGB/Component Video (D-Sub)x2, Composite Video (RCA)x1, HDMI, HDMI/HML, PC Audio Output : DC Out (5V/2A, USB Type A)x1, PC Audio, Analog RGB (D-sub) Colour : White	**670**
X1227i 	Display Panel : DLP® Resolution : XGA (1,024x 768) Maximum WUXGA (1,920x1,200) Aspect Ratio : 4:3 (Native),16:9 (Supported) Contrast Ratio : 20,000:1 Dynamic Black Brightness : 4,000 ANSI Lumens (Standard), 3,200 ANSI Lumens (Eco) Lamp Life : 6,000 Hours (Standard), 10,000 Hours (ECO) 15,000 Hours (ExtremeEco) Keystone Correction : +/- 40 Degree (Vertical ,Manual & Auto), +/- 20 Degree (Horizontal ,Manual), 4-Corner adjustment Throw Ratio : 1.94 to 2.16 (51"@2m) Input : Analog RGB/Component Video(D-Sub)x1,HDMI(video,Audio,HDCP)x1 : PC Audio(Stereo mini jack)x1composite video(RCA)x1USB Type Ax1,For Wireless Dongle Output : DC Out (5V/2A, USB Type A)x1, PC Audio (Stereo mini jackx1) Colour : Black	**459**
X1228H 	Display Panel : DLP® Resolution : XGA (1,024 x 768) Maximum WUXGA (1,920x1,200) Aspect Ratio : 4:3 (Narive)/16:9 (Supported) Contrast Ratio : 20,000:1 Brightness : 4,500 ANSI Lumens (Standard), 3,600 ANSI Lumens (Eco) Lamp Life : 6,000 Hours (Standard), 10000 Hours (ECO) 15,000 Hours (ExtremeEco) Keystone Correction : +/- 40 Degree (Vertical ,Manual & Auto), +/- 20 Degree (Horizontal ,Manual), 4-Corner adjustment Throw Ratio : 1.94 to 2.16 (51"@2m) Input : Analog RGB/Component Video(D-Sub)x1,HDMI(video,Audio,HDCP)x1 : PC Audio(Stereo mini jack)x1composite video(RCA)x1 Output : PC Audio (Stereo mini jackx1)DC Out (5V/2A, USB Type A)x1, Analog RGB (D-sub) Colour : Black	**379**
X1226AH 	Display Panel : DLP®3D Ready Resolution : XGA (1,024 x 768) Maximum WUXGA (1,920x1,200) Aspect Ratio : 4:3 (Native), 16:9 (Supported) Contrast Ratio : Dynamic Black 20,000:1 Brightness : 4,000 ANSI Lumens (Standard) 3,200 ANSI Lumens (Eco) **(Compliant with ISO 21118 Standard)** Lamp Life : 4,500 Hours (Standard),10,000 Hours (ECO) 15,000 Hours (ExtremeEco) Keystone Correction : +/- 40 Degree (Vertical ,Manual & Auto) Throw Ratio : 1.94~2.16 (51"@2m) Input : Analog RGB/Component Video (D-Sub), RCA, S-Video, HDMI, PC Audio Output : RGB, DC Out, PC Audio Colour : Black	**419**